

Page : 1
Revised edition no : 5

Date: 30 / 11 / 2012

Supersedes: 26 / 9 / 2012

## **AZETHYL - 5% ETHYLENE NITROGEN**

**AL084** 

**Danger** 





### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : AZETHYL - 5% ETHYLENE NITROGEN

**SDS Nr** : AL084

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.

Test gas / Calibration gas. Laboratory use Contact supplier for more uses information

#### 1.3. Details of the supplier of the safety data sheet

Company identification : Air Liquide Australia Limited

Level 9 / 380 St. Kilda Road Melbourne VIC 3004 Australia Tel: + 61 3 9697 9888 Fax: + 61 3 9690 7107

ALAEnquiries@AirLiquide.com

## 1.4. Emergency telephone number

Emergency telephone number : 1800 812 588

### **SECTION 2. Hazards identification**

### 2.1. Classification of the substance or mixture

## Hazard Class and Category Code Regulation EC 1272/2008 (CLP)

• Physical hazards : Flammable gases - Category 1 - Danger - (CLP : Flam. Gas 1) - H220

Gases under pressure - Compressed gas - Warning - (CLP : Press. Gas) - H280

Classification EC 67/548 or EC 1999/45

: F+; R12

### 2.2. Label elements

#### Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms





• Hazard pictograms code : GHS02 - GHS04

• Signal word : Danger

• Hazard statements : H220 - Extremely flammable gas.

H280 - Contains gas under pressure; may explode if heated.

• Precautionary statements

Prevention
 Response
 P210 - Keep away from heat, sparks, open flames or hot surfaces. – No smoking.
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 - Eliminate all ignition sources if safe to do so.

- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

: None.

Air Liquide Australia Limited

Level 9 / 380 St. Kilda Road Melbourne VIC 3004 Australia

Tel: + 61 3 9697 9888 Fax: + 61 3 9690 7107 ALAEnquiries@AirLiquide.com



Page : 2

Revised edition no : 5

Date : 30 / 11 / 2012

Supersedes: 26 / 9 / 2012

## **AZETHYL - 5% ETHYLENE NITROGEN**

**AL084** 

## **SECTION 2. Hazards identification (continued)**

#### **SECTION 3. Composition/information on ingredients**

#### 3.1. Substance / 3.2. Mixture

Mixture.

 Substance name
 Contents
 CAS No
 EC No
 Annex No
 Classification

 Ethylene
 : <= 5 %</td>
 74-85-1
 200-815-3
 601-010-00-3
 \* 2
 F+; R12 R67 R67 R67

Flam. Gas 1 (H220) STOT RE 3 (H336) Lig. Gas (H280)

Contains no other components or impurities which will influence the classification of the product.

- \* 1: Listed in Annex IV / V REACH, exempted from registration.
- \* 2: Registration deadline not expired.
- \* 3: Registration not required: Substance manufactured or imported < 1t/y
  Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

#### **SECTION 4. First aid measures**

### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

- Skin contact : Adverse effects not expected from this product.
- Eye contact : Adverse effects not expected from this product.

- Ingestion : Ingestion is not considered a potential route of exposure.

#### 4.2. Most important symptoms and effects, both acute and delayed

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/

consciousness. Victim may not be aware of asphyxiation.

Refer to section 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed

: None.

### **SECTION 5. Fire-fighting measures**

#### 5.1. Extinguishing media

- Suitable extinguishing media : All known extinguishants can be used.

## 5.2. Special hazards arising from the substance or mixture

**Specific hazards** : Exposure to fire may cause containers to rupture/explode. **Hazardous combustion products** : Incomplete combustion may form carbon monoxide.

## 5.3. Advice for fire-fighters

Specific methods : Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive

re-ignition may occur. Extinguish any other fire.

Coordinate fire measure to the surrounding fire. Cool endangered containers with water spray jet from a protected position. Do not empty contaminated fire water into drains

jet from a protected position. Do not empty contaminated fire water into drains.

If possible, stop flow of product.

Special protective equipment for fire

fighters

: In confined space use self-contained breathing apparatus.

Air Liquide Australia Limited

Level 9 J 380 St. Kilda Road Melbourne VIC 3004 Australia Tel: + 61 3 9697 9888

Fax: + 61 3 9690 7107 ALAEnquiries@AirLiquide.com



Page: 3 Revised edition no: 5

Date: 30 / 11 / 2012

Supersedes: 26 / 9 / 2012

## **AZETHYL - 5% ETHYLENE NITROGEN**

**AL084** 

#### SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

: Evacuate area.

Try to stop release.

Ensure adequate air ventilation. Eliminate ignition sources.

Consider the risk of potentially explosive atmospheres.

#### 6.2. Environmental precautions

: Try to stop release.

#### 6.3. Methods and material for containment and cleaning up

: Ventilate area.

### 6.4. Reference to other sections

: See also sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Safe use of the product

: Take precautionary measures against static discharge.

Purge air from system before introducing gas.

Keep away from ignition sources (including static discharges).

Do not smoke while handling product.

Assess the risk of potentially explosive atmosphere and the need for explosion-proof

equipment.

Consider the use only non-sparking tools.

Use only properly specified equipment which is suitable for this product, its supply pressure

and temperature. Contact your gas supplier if in doubt.

Only experienced and properly instructed persons should handle gases under pressure. The product must be handled in accordance with good industrial hygiene and safety

procedures.

Ensure the complete gas system was (or is regularily) checked for leaks before use.

### Safe handling of the gas receptacle

: Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect cylinders from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.)

designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall

or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating cylinder valve discontinue use and contact

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminates particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is

disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder

### 7.2. Conditions for safe storage, including any incompatibilities

Segregate from oxidant gases and other oxidants in store.

All electrical equipment in the storage areas should be compatible with the risk of potentially explosive atmosphere.

Keep away from combustible materials.

Keep container below 50℃ in a well ventilated place.

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Containers should be stored in the vertical position and properly secured to prevent toppling. Stored containers should be periodically checked for general condition and leakage.

Container valve guards or caps should be in place.

#### Air Liquide Australia Limited

Fax: +61 3 9690 7107 ALAEnquiries@AirLiquide.com



Page: 4

Revised edition no: 5 Date: 30 / 11 / 2012

Supersedes: 26 / 9 / 2012

## **AZETHYL - 5% ETHYLENE NITROGEN**

**AL084** 

## SECTION 7. Handling and storage (continued)

Store containers in location free from fire risk and away from sources of heat and ignition.

7.3. Specific end use(s)

: None.

#### SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

**DNEL: Derived no effect level** : None available. PNEC: Predicted no effect : None available.

concentration 8.2. Exposure controls

8.2.1. Appropriate engineering

controls

Systems under pressure shoud be regularily checked for leakages.

Provide adequate general and local exhaust ventilation.

Gas detectors should be used when flammable gases/vapours may be released.

Keep concentrations well below lower explosion limits.

Ensure exposure is below occupational exposure limits (where available).

Consider work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, :

e.g. personal protective equipment

Consider the use of flame resistant anti-static safety clothing.

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered.

Wear safety glasses with side shields

Wear leather safety gloves and safety shoes when handling cylinders.

8.2.3. Environmental exposure

controls

: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

## SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

**Appearance** 

- Physical state at 20℃ / 101.3kPa : Gas.

- Colour : Colourless gas.

Odour : No odour warning properties.

**Odour threshold** : Odour threshold is subjective and inadequate to warn for overexposure.

: Not applicable for gases and gas-mixtures. pH value : Not applicable for gases and gas-mixtures. Molar mass [g/mol] Melting point [℃] : Not applicable for gas-mixtures.

Boiling point [℃] : Not applicable for gas-mixtures. : Not applicable for gas-mixtures. Flash point [℃] Evaporation rate (ether=1) : Not applicable for gas-mixtures. Flammability range [vol% in air] : Not applicable for gas-mixtures.

Vapour pressure [20℃] : Not applicable. Relative density, gas (air=1) : Lighter or similar to air.

Solubility in water [mg/l] : Not known, but considered to have low solubility.

Partition coefficient n-octanol/water : Not applicable for gas-mixtures.

Viscosity at 20℃ [mPa.s] : Not applicable. **Explosive Properties** : Not applicable.

9.2. Other information

Other data : None.

Air Liquide Australia Limited

Level 9 / 380 St. Kilda Road Melbourne VIC 3004 Australia Tel: + 61 3 9697 9888

Fax: + 61 3 9690 7107 ALAEnquiries@AirLiquide.com



Page : 5

Revised edition no : 5

Date : 30 / 11 / 2012

Supersedes : 26 / 9 / 2012

## **AZETHYL - 5% ETHYLENE NITROGEN**

**AL084** 

## **SECTION 10. Stability and reactivity**

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions

: May react violently with oxidants. Can form explosive mixture with air.

10.4. Conditions to avoid

: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

10.5. Incompatible materials

: May react violently with oxidants.

10.6. Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11. Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity : No known toxicological effects from this product.

Rat inhalation LC50 [ppm/4h] : No data available.

Skin corrosion/irritation : No known effects from this product. Serious eye damage/irritation : No known effects from this product. Respiratory or skin sensitisation : No known effects from this product. Carcinogenicity : No known effects from this product. : No known effects from this product. Germ cell mutagenicity Toxic for reproduction : Fertility : No known effects from this product. Toxic for reproduction: unborn child: No known effects from this product. : No known effects from this product. STOT-single exposure : No known effects from this product. STOT-repeated exposure **Aspiration hazard** : Not applicable for gases and gas-mixtures.

## **SECTION 12. Ecological information**

12.1. Toxicity

: No data available.

12.2. Persistence - degradability

: No data available.

12.3. Bioaccumulative potential

: No data available.

12.4. Mobility in soil

: No data available.

12.5. Results of PBT and vPvB assessment

: No data available.

12.6. Other adverse effects

Effect on ozone layer : None.

Air Liquide Australia Limited

Level 9 / 380 St. Kilda Road Melbourne VIC 3004 Australia

Tel: + 61 3 9697 9888 Fax: + 61 3 9690 7107 ALAEnquiries@AirLiquide.com



Page: 6

Revised edition no: 5 Date: 30 / 11 / 2012

Supersedes: 26 / 9 / 2012

## **AZETHYL - 5% ETHYLENE NITROGEN**

**AL084** 

### **SECTION 12. Ecological information (continued)**

: No known ecological damage caused by this product. Effect on the global warming

## **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

: Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous.

Ensure that the emission levels from local regulations or operating permits are not exceeded.

Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at http:// www.eiga.org) for more guidance on suitable disposal methods

Contact supplier if guidance is required.

#### 13.2. Additional information

: None.

## **SECTION 14. Transport information**

**UN** number : 1954

Labelling ADR, IMDG, IATA

: 2.1 : flammable gas.

#### Land transport (ADR/RID)

H.I. nr : 23

: COMPRESSED GAS, FLAMMABLE, N.O.S. (Ethylene, Nitrogen) **UN proper shipping name** 

Transport hazard class(es) : 2 : 1 F Classification code Packing Instruction(s) : P200

**Tunnel Restriction** : B/D Tank carriage: Passage forbidden through tunnels of category B, C, D

**HAZCHEM - Emergency Action Code** 

2 = Fine water spray.

S = Risk of violent reaction or explosion. Recommended personal protective equipment : Full

fire kit and breathing apparatus. Appropriate measures : dilute.

E = There may be a public safety hazard outside the immediate area of the incident, and that

the following actions should be considered:

1. People should be warned to stay indoors with all doors and windows closed, preferably in rooms upstairs and facing away from the incident. Ignition sources should be eliminated and any ventilation stopped.

2. Effects may spread beyond the immediate vicinity. all non-essential personnel should be

instructed to move at least 250 metres away from the incident.

3. Police and fire brigade incident commanders should consult each other and with a product

expert, or with a source of product expertise.

4. The possible need for subsequent evacuation should be considered, but it should be remembered that in most cases it will be safer to remain in a building than to evacuate.

### Sea transport (IMDG)

Proper shipping name : COMPRESSED GAS, FLAMMABLE, N.O.S. (Ethylene, Nitrogen)

Emergency Schedule (EmS) - Fire : F-D Emergency Schedule (EmS) - Spillage : S-U **Packing instruction** : P200

#### Air Liquide Australia Limited

Fax: + 61 3 9690 7107 ALAEnquiries@AirLiquide.com



Page: 7 Revised edition no: 5

Date: 30 / 11 / 2012

Supersedes: 26 / 9 / 2012

## **AZETHYL - 5% ETHYLENE NITROGEN**

**AL084** 

#### SECTION 14. Transport information (continued)

#### Air transport (ICAO-TI / IATA-DGR)

Proper shipping name (IATA) : COMPRESSED GAS, FLAMMABLE, N.O.S. (Ethylene, Nitrogen)

Class : 2.1

: DO NOT LOAD IN PASSENGER AIRCRAFT. Passenger and Cargo Aircraft

Cargo Aircraft only : Allowed. Packing instruction - Cargo Aircraft : 200

only

### Special precautions for user

: Avoid transport on vehicles where the load space is not separated from the driver's

compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

- Ensure valve protection device (where provided) is correctly fitted.

## **SECTION 15. Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** legislation

: Covered Seveso directive 96/82/EC

**National legislation** 

: Ensure all national/local regulations are observed.

#### 15.2. Chemical Safety Assessment

: A CSA does not need to be carried out for this product.

#### SECTION 16. Other information

Indication of changes : Revised safety data sheet in accordance with commisssion regulation (EU) No 453/2010

Training advice Ensure operators understand the flammability hazard.

Receptacle under pressure.

List of full text of R-phrases in section :

R12 : Extremely flammable. R67 : Vapours may cause drowsiness and dizziness.

List of full text of H-statements in

section 3.

H220 - Extremely flammable gas.

H280 - Contains gas under pressure; may explode if heated.

H336 - May cause drowsiness or dizziness.

Further information Classification in accordance with calculation methods of regulation (EC) 1272/2008 CLP / (

EC) 1999/45 DPD.

This Safety Data Sheet has been established in accordance with the applicable European

Union legislation.

**DISCLAIMER OF LIABILITY** : Before using this product in any new process or experiment, a thorough material compatibility

and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or

damage resulting from its use can be accepted.

The contents and format of this SDS are in accordance with EC Commission Directive 2001/58/EC.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way

Air Liquide Australia Limited

Level 9 / 380 St. Kilda Road Melbourne VIC 3004 Australia

Tel: + 61 3 9697 9888 Fax: + 61 3 9690 7107 ALAEnquiries@AirLiquide.com



Page: 8
Revised edition no: 5

Date: 30 / 11 / 2012 Supersedes: 26 / 9 / 2012

# **AZETHYL - 5% ETHYLENE NITROGEN**

**AL084** 

In case of emergency: 1800 812 588

connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document